

MU-1 SLD A

SPECIFICATIONS

| | |
|------------------------------|--|
| Nominal Voltage (V) | 12V |
| Capacity at C/100 | 37Ah |
| Capacity at C/20 | 32Ah |
| Capacity at C/5 | 27.5 Ah |
| Weight | 23 lbs. (10 kg) |
| Plate Alloy | Lead Calcium |
| Posts | Forged Terminals & Bushings |
| Container/Cover | Polypropylene |
| Operating Temperature Range | -40°F (-40°C) - 140°F (60°C) |
| Charge Voltage @ 77°F (25°C) | |
| Cycle Float | 13.8 - 14.6 volts 13.4 - 13.6 volts |
| Vent | Self-sealing |
| Terminal | Y (T873) |



Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co., Inc.

Distributed by:

Valve-Regulated, Absorbed Glass Mat Technology




DIMENSIONS

Inches (mm)

| | |
|--------|--|
| Length | 8.41 (214 mm) |
| Width | 5.21 (132 mm) |
| Height | 7.33 (186 mm) <i>Including terminal</i> |

AGM Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

